



CS-Series

The CS-Series from Wicks and Wilson is a range of high volume production scanners for digitising microfilm aperture cards. These scanners are designed to meet the demands of large scale scanning projects with the minimum of operator intervention and maximum productivity.



CS-Series Microfilm Aperture Card Scanning Systems
the easier, simpler, better way to scan microfilm

Key Features and Technical Specifications

CS-Series Aperture Card Scanners

- Automated 500 card horizontal input hopper for simple loading and reliable card feed.
- Smartscan, the Wicks and Wilson designed 12-bit image processing system for microfilm, provides real-time control of on-board advanced imaging tools for both bitonal and 256-level greyscale imaging.
- Hollerith (punch data) automatically read and used to select drawing sizes and create file names if required.
- Robust and proven mechanical design, for reliable operation during extended production runs.
- Production tools include manual rotation, framing, cropping and deskew as well as automatic log file generation.
- Optional production tools maximise the efficiency and productivity of the scanner:

Auto deskew and centring* straightens and repositions the drawing prior to saving

Multi Scan enables a single card to be automatically rescanned using up to five different imaging templates

Greyscale provides a 256 level output, giving the best results from poor quality cards

DMP (Digital Microfilm Printing) offers a simplified user screen featuring digital zoom and review before printing; interfaces to any printer or plotter with a Windows- certified driver

Model	CS500	CS750
Resolution	100 - 400 dpi	100 - 600 dpi
Speed (A2 / C Size, 200dpi)	500 cards per hour	750 cards per hour
Speed (A2 / C Size, 400dpi)	300 cards per hour	620 cards per hour
Hopper-feed	500 card automated batch feed	500 card automated batch feed
Output hoppers	Optional	150 card Review 150 card Reject
Reduction ratio (fixed focus)	7.5x to 36x (variable)	
Film types	Silver and diazo	
Drawing sizes	User Defined, within limits of tape window	
Scaling accuracy	+/- 0.5 %	
Bitonal output file format	TIFF (G3 or G4) and CALS	
Greyscale output file format**	JPEG, BMP, RAW TIFF	
Agency approvals	CE, TÜV, UL, cUL	
RoHS compliance	YES	
Size (WxDxH)	890mm x 400mm x 430mm (35" x 16" x 17")	
Weight	40kg (88lbs)	
Power requirements	120/230Volts, 2.3/1.2 Amps	
PC connection	Dedicated PCI interface card supplied (full height slot required)	
Operating system	Windows XP Professional, SP2	
Controller PC specification	Please see WWL website for current PC requirements www.wwl.co.uk	

* Bitonal only

** Greyscale output available as an option

Rev 02/08

Wicks and Wilson Limited, Morse Road, Basingstoke, Hampshire, RG22 6PQ, United Kingdom

Telephone: +44 (0)1256 842211 Fax: +44 (0)1256 840997

Email: sales@wwl.co.uk Web: www.wwl.co.uk

Wicks and Wilson Limited pursues a policy of continuous product improvement and reserves the right to change these specifications without notice.

All Wicks and Wilson products are distributed worldwide. For details of your nearest distributor please visit our website.



BS EN ISO 9001:2000
Reg No. FM01740